



Logic Analyzers

TLA 700 Series



Features and Benefits

MagniVu™ Acquisition Technology Provides 500 ps Timing Resolution on All Channels All the Time Through a Single Probe

Up to 200 MHz State Acquisition with 400 MHz Data Rate Supports Advanced Processors and Buses

Simultaneous State and High Speed Timing Analysis Through the Same Probes Pinpoints Elusive Integration Faults

64 Channel Pattern Generator with up to 268 MHz and up to 2 MB Memory Depth Provides Digital Stimulus for Functional Verification, Debugging and Stress Testing

Four Channel Digitizing Oscilloscope with up to 1 GHz, 5 GS/s Provides High-fidelity Signal Quality Measurements of Digital Signals

Expansion Mainframe Supports up to 16 Modules with up to 2,176 LA channels, 1,024 Pattern Generator Channels or 64 Digitizing Oscilloscope channels for Large, Multiple Processor and Bus Applications

Microsoft® Windows®-based PC Platform Provides Familiar User Interface With Network Connectivity

Applications

Hardware Debug and Verification
Processor/Bus Debug and Verification
Embedded Software Integration, Debug and Verification

Embedded Real-time Software Optimization
System Validation

BREAKTHROUGH SOLUTIONS FOR REAL-TIME DIGITAL SYSTEMS ANALYSIS

Today's digital design engineers face daily pressures to speed new products to the marketplace. The TLA 700 Series answers the need with breakthrough

solutions for the entire design team, providing the ability to quickly monitor, capture and analyze real-time system operation in order to debug, verify, optimize and validate digital systems.

Tektronix®



Logic Analyzer Modules

GENERAL

Number of Channels per Module (all channels are acquired including clocks) –

TLA 7N1: 34 channels (2 are clock/qualifier channels).

TLA 7N2, TLA 7P2: 68 channels (4 are clock/qualifier channels).

TLA 7N3: 102 channels (4 are clock/qualifier and 2 are qualifier channels).

TLA 7N4, TLA 7P4: 136 channels (4 are clock/qualifier and 4 are qualifier channels).

Channel Grouping – No limit to number of groups or number of channels per group (all channels can be reused in multiple groups).

Module “Merging” – Three 102 channel or 136 channel modules can be “merged” to make up to a 408 channel module. Merged modules exhibit the same depth as the lesser of the three individual modules. Word/range/setup-and-hold/glitch/transition recognizers span all three modules. Only one set of clock connections is required.

Time Stamp – 50 Bits at 500 ps resolution (6.5 day range).

Clocking/Acquisition Modes- State, timing, simultaneous.

Number of Mainframe Slots Required – 2.

INPUT CHARACTERISTICS (WITH P6417, P6418 OR P6434 PROBES)

Capacitive Loading –

1.4 pF typical data; 2 pF typical clock (P6418). 2 pF typical (P6417 & P6434).

Threshold Selection Range – From +5.0 V to –2.0 V in 50 mV increments.

Threshold Selection Channel Granularity – Separate selection for clock (1) and data (16) for each 17 channel probe connector.

Threshold Accuracy (including probe) – ±100 mV.

Input Voltage Range –

Operating: 6.5 V_{p,p} centered around the programmed threshold.

Non-destructive: ±15 V.

Input Signal Swing (probe overdrive) –

±250 mV or ±25% of signal swing, whichever is greater (P6417 & P6418).

±300 mV or ± 25% of signal swing (P6434).

Input Signal Minimum Slew Rate –

200 mV/ns typical.

STATE ACQUISITION CHARACTERISTICS (WITH P6417, P6418 OR P6434 PROBES)

Maximum Synchronous Clock Rate –

100 MHz standard, 200 MHz optional.

Maximum Data Rate (Half Channels) – 400 MHz, typical. Requires 200 MHz state option.

State Memory Depth – 64 K, 256 K, 1 M, 4 M or 16 M bits per channel.

Setup Time Selection Range – From 8.5 ns before, to 7.0 ns after clock edge.

Setup-and-hold Window – 2.0 ns typical.

Minimum Clock Pulse Width – 2 ns.

Active Clock Edge Separation – 5 ns.

Demux Channel Selection – 32 channels can be demultiplexed to other channels through user interface; for all channels contact local Tektronix account manager.

TIMING ACQUISITION CHARACTERISTICS (WITH P6417, P6418 OR P6434 PROBES)

Main Timing Resolution – 4 ns to 50 ms.

Main Timing Resolution with Glitch Storage Enabled – 10 ns to 50 ms.

Main Timing Memory Depth (with or without transitional storage enabled) – 64 K, 256 K, 1 M, 4 M or 16 M bits per channel.

Main Timing Memory Depth with Glitch Storage Enabled – Half of default main memory depth.

MagniVu – 500 ps.

MagniVu Timing Memory Depth – 2 Kbits (2048) per channel.

Channel-to-channel Skew – ≤1 ns typical.

Minimum Recognizable Pulse Width (single channel) – 2 ns.

Minimum Recognizable Glitch Width (single channel) – 2 ns.

Minimum Recognizable Multi-channel Trigger Event – Sample period + 2 ns.

TRIGGER CHARACTERISTICS

Independent Trigger States – 16.

Maximum Independent If/then Clauses per State – 16.

Maximum Number of Events per If/then Clause – 8.

Maximum Number of Actions per If/then Clause – 8.

Maximum Number of Trigger Events – 18 (2 counter/timers plus any 16 other resources).

Number of Word Recognizers – 16.

Number of Range Recognizers – 4.

Number of Counter/Timers – 2.

Trigger Event Types – Word, group, channel, transition, range, anything, counter value, timer value, signal, glitch, setup-and-hold violation.

Trigger Action Types – Trigger module, trigger all, store, don't store, start store, stop store, increment counter, reset counter, start timer, stop timer, reset timer, goto state, set/clear signal, do nothing.

Trigger Sequence Rate – DC to 250 MHz (4 ns).

Counter/Timer Range – 51 bits each (>100 days @ 4 ns).

Counter Rate – DC to 250 MHz (4 ns).

Timer Clock Rate – 250 MHz (4 ns).

Counter/Timer Latency – None (can be tested or reset immediately after starting).

Range Recognizers – Double bounded (can be as wide as any group, must be grouped according to specified order of significance).

Setup-and-hold Violation Recognizer Setup Time Range – From 8 ns before to 7 ns after clock edge in 0.5 ns increments.

Setup-and-hold Violation Recognizer Hold Time Range – From 7 ns before to 8 ns after clock edge in 0.5 ns increments.

Trigger Position – Any data sample.

MagniVu Trigger Position – MagniVu data is centered around the module trigger.

Storage Control (data qualification) – Global (conditional), by state (start/stop), by trigger action, or transitional.

Storage Window Granularity – Single sample or block-of-31 samples before and after.

Logic Analyzer Module Physical Characteristics

Dimensions

Dimensions	mm	in.
Height	262	10.3
Width	61	2.4
Depth	381	15
Weight	kg	lb.
Net	3.1	6.7
Shipping	6.3	13.7

P6417 Probe Cable Length – 1.8 m (6 ft.).

P6418 Probe Cable Length – 1.9 m (6.25 ft.).

P6434 Probe Cable Length – 1.5 m (5 ft.).

All three probes have the same electrical length.

Pattern Generator Module

GENERAL

Data Width –

64 Channel full channel mode.

32 Channel half channel mode.

Module “Merging” – Five modules can be “merged” to make up to a 320 channel module. Merged modules exhibit the same depth as the lesser of the 5 individual modules.

Number of Mainframe Slots Required – 2.

Data Rate –

Internal Clock:

0.5 Hz to 134 MHz full channel mode.

1.0 Hz to 268 MHz half channel mode.

External Clock:

DC to 134 MHz full channel mode.

DC to 268 MHz half channel mode.

External Clock Input –

Polarity: positive or negative.
 Threshold: -2.56 V to +2.54 V, nominal; programmable in 20 mV increments.
 Sensitivity: $\leq 500 \text{ mV}_{p-p}$.
 Impedance: 1 k Ω terminated to ground.

Data Depth –

256 K full channel/512 K half channel.
 1 M full channel/2 M half channel (optional).

PATTERN SEQUENCING CHARACTERISTICS

Blocks – Separate sections of pattern program that are output in a user definable order by the Sequencer. Block pattern depth can be from 40 sequences (full channel mode) or 80 sequences (half channel mode) up to the entire depth of the TLA 7PG2. A maximum of 4,000 Blocks may be defined.

Sequencer – A 4000 line memory that allows the user to pick the output order of individual Blocks. Each line in the sequencer allows the definition of a Block to be output, a Repeat Count for that Block, A Wait For event condition for the Block, the Signal state for that Block (asserted or unasserted), and a Jump If event condition, with a sequence line to jump to if the condition is satisfied.

Sub-Sequences – Up to 50 contiguous lines of the Sequencer memory may be defined as a Sub-Sequence. A Sub-Sequence can then be treated like a block. (Example: 15 Sequences of Blocks are defined as Sub-Sequence A1. Now any line in the Sequencer can output A1. Five calls to Sub-Sequence A1 will be flattened out to 75 sequences at run time.)

Jump If – Jumps to the specified sequence if a user defined event is true. The user defined event is a boolean combination of the eight external event input lines and the one-of-four intermodule signals. The user defined Event is selectable between level and edge (event going from false to true). One Jump If may be defined for every Block. The Jump If command works at all clock rates, including the maximum half channel mode rate of 268 MHz.

Wait For – Pattern output is paused until the user defined Event is true. One Wait For may be defined for every Block.

Assert Signal – One of the four inter-module signals is selected to be controlled from the pattern generator program. Signals may be asserted and unasserted allowing true interaction with the logic analyzer modules and with other pattern generator modules. Signal action (assert or unassert) may be defined for every Block.

Repeat Count – The sequence is repeated from 1 to 65,536 times. Infinite may also be selected. One Repeat Count may be defined for every Block. Note that a Repeat value of 10,000 takes one sequence line in memory, not 10,000.

Step – While in Step mode, the TLA 7PG2, the user can manually satisfy (i.e., click an icon) Wait For and Jump conditional events. This allows the user to debug the logic flow of the program's sequencing.

Initialization Block – The unconditional Jump command allows the user to implement an equivalent function.

COMMON TO P6470 TTL/CMOS & P6471 ECL PROBES

Number of Data Outputs –

16 in Full Channel Mode.
 8 in Half Channel Mode.

Number of Clock Outputs – 1.

(Only one of Clock Output and Strobe Output can be enabled.)

Number of Strobe Outputs – 1.

(Only one of Clock Output and Strobe Output can be enabled.)

Number of External Event Input – 2.

Clock Output Polarity – Positive.

Strobe Type – RZ only.

Strobe Delay – Zero or Trailing Edge.

P6470 TTL/CMOS PROBE

Output Type –

HD74LVC541A for Data Output.
 HD74LVC244A for Clock/Strobe Output.

Rise/Fall Time (20% to 80%) –

	Timing values measured using 75 Ω termination (internal to probe), 1 M Ω + <1 pF load and V _{OH} set to 5.0 V	Timing values measured using 75 Ω termination (internal to probe), 510 Ω + 51 pF load and V _{OH} set to 5.0 V
Clock/Strobe Output:		
Rise:	640 ps typical	6.5 ns typical
Fall:	1.1 ns typical	6.3 ns typical
Data Output:		
Rise:	680 ps typical	5.2 ns typical
Fall:	2.9 ns typical	4.5 ns typical

Clock/Strobe Output:		
Rise:	640 ps typical	6.5 ns typical
Fall:	1.1 ns typical	6.3 ns typical
Data Output:		
Rise:	680 ps typical	5.2 ns typical
Fall:	2.9 ns typical	4.5 ns typical

Output Voltage (nominal, load: 1 M Ω) –

V_{OH}: 2.0 V to 5.5 V, tri-stateable, programmable in 25 mV increments.

V_{OL}: 0 V.

Data Output Skew –

< 510 ps typical between all data output pins of all modules in the mainframe after inter-module skew is adjusted manually.

< 480 ps typical between all data output pins of single probe.

Data Output to Strobe Output Delay –

1.7 ns typical when strobe delay set to zero.

Data Output to Clock Output Delay –

2.4 ns typical.

External Clock Input to Clock Output Delay –

Delay –

Full Channel mode: 61.5 ns typical.

Half Channel mode: 61.5 ns typical.

Number of External Inhibit Input – 1.

External Inhibit Input to Output Enable Delay –

34 ns typical for Data Output.

External Inhibit Input to Output Disable Delay –

86 ns typical for Data Output.

Probe D Data Output to Output Enable Delay –

(for Internal Inhibit) 7 ns typical for Data Output.

Probe D Data Output to Output Disable Delay –

(for Internal Inhibit) 8 ns typical for Data Output.

External Event Input to Clock Output Setup (for inhibit) (event-filter: off) –

Full Channel mode: 1.5 clocks + 150 ns typical.

Half Channel mode: 2 clocks + 150 ns typical.

External Event Input and Inhibit Input –

Input Type: 74LVC14A.

Minimum Pulse Width: 100 ns.

P6471 ECL PROBE

Output Type –

100E151 for data output.

100EL16 for strobe output.

100EL04 for clock output.

All outputs are uninterminated.

Rise/Fall Time (20% to 80%) –

Timing values measured using 51 Ω s to -2.0 V

Clock Output:		
Rise:	320 ps typical	
Fall:	330 ps typical	
Data Output:		
Rise:	1200 ps typical	
Fall:	710 ps typical	
Strobe Output:		
Rise:	290 ps typical	
Fall:	270 ps typical	

Data Output Skew –

<170 ps typical between all data output pins of all modules in the mainframe after inter-module skew is adjusted manually.

<140 ps typical between all data output pins of single probe.

Data Output to Strobe Output Delay –

2.94 ns typical when strobe delay set to zero.

Data Output to Clock Output Delay –

780 ps typical.

External Clock Input to Clock Output Delay –

51 ns typical.

External Event Input –

Input Level: ECL.

Input Type: 10H116.

Minimum Pulse Width: 50 ns.

Pattern Generator Module

Physical Characteristics

Dimensions	mm	in.
Height	262	10.3
Width	61	2.4
Depth	381	15
Weight	kg	lb.
Net	3.0	6.5
Shipping	6.2	13.5

P6470 Probe Cable Length – 1.6 m (5 ft.)

P6471 Probe Cable Length – 1.6 m (5 ft.)

Digitizing Oscilloscope Modules

GENERAL

Number of Channels per Module –

TLA 7D2, TLA 7E2: 4 channels.
TLA 7D1, TLA 7E1: 2 channels.

Sample Rate –

TLA 7E1, TLA 7E2: 5 GS/s on all channels.
TLA 7D1, TLA 7D2: 2.5 GS/s on all channels.

Bandwidth (at probe tips) –

TLA 7E1, TLA 7E2:
100 mV to 10 V range: 1 GHz.
50 mV to 99.8 mV range: 900 MHz.
20 mV to 49.8 mV range: 600 MHz.

All others:

500 MHz.
TLA 7D1, TLA 7D2: 500 MHz on all channels in all ranges.

Memory Depth –

15,000 samples per channel in all modes.

Number of Mainframe Slots Required – 2.

VERTICAL SYSTEM

Input Sensitivity Range – 10 mV to 100 V full scale.

Vertical Resolution – 8 bits (256 levels).

DC Gain Accuracy – $\pm 1.5\%$ of full scale range.

Analog Bandwidth Selections – 20 MHz, 250 MHz, and Full.

Input Coupling – AC, DC, or GND.

Input Impedance Selections – 1 M Ω in parallel with 10 pF, or 50 Ω .

AC Coupled Lower Frequency Limit – ≤ 10 Hz when AC 1 M Ω coupled, ≤ 200 kHz when AC 50 Ω coupled.

Maximum Input Voltage at Probe

Connector – 300 VRMS, but no greater than ± 420 V peak (1 M Ω or ground input coupling).

PROBE INPUT CHARACTERISTICS

Probe Input Interface – TEKPROBE™ probe interface.

Input Loading – Less than 1 pF in parallel with 1 M Ω with either P6243 or P6245.

Usable Input Voltage Range at Probe Tip - P6243 Probe: ± 8 V. P6245 Probe: ± 18 V.

ACQUISITION SYSTEM

Sample Rate Range – 200 ps to 200 ms in 1, 2.5, 5 sequence.

Timebase Accuracy – ± 100 ppm over any interval ≥ 1 ms.

Record Length Range – 512 to 15,000 samples per channel in all modes.

Acquisition Modes – Single-shot, repetitive.

TRIGGER SYSTEM

Trigger Modes – Normal, auto.

Trigger Position – Anywhere in the acquired record (pre-fill can be set anywhere from 0% to 100%).

Trigger Types – Edge, pulse width, timeout, glitch, runt, slew rate, logic pattern, setup-and-hold violation.

Trigger Actions – Trigger, trigger all, set signal, arm, immediate, wait for system trigger.

Edge Trigger – Conventional level driven trigger, positive or negative slope, on any channel or external trigger input. Coupling Selections: DC, AC, noise reject, HF reject, LF reject.

Pulse Width Trigger – Trigger on width of positive or negative pulse, either within or not within selectable time limits; settable from 2 ns to 1 s.

Timeout Trigger – Triggers when a pulse fails to complete when specified; settable from 2 ns to 1 s.

Glitch Trigger – Trigger on (or reject) glitches of positive, negative, or either polarity; settable from 2 ns to 1 s. Minimum glitch width: 2.0 ns, with 200 ps resolution (2 ns to 10 ns settings).

Runt Pulse Trigger – Trigger on a pulse that crosses one threshold but fails to cross a second threshold before crossing the first again; settable from 2 ns to 1 s.

Slew Rate Trigger – Trigger on pulse edge rates that are either faster or slower than a set rate, edges can be rising, falling, or either; settable from 2 ns to 1 s.

Logic Pattern Trigger – Triggers when a logical combination (AND, OR) of all the input channels (Hi, Lo, Don't Care) stays true or false for a specified period of time; settable from 2 ns to 1 s.

Setup-and-hold Trigger – Trigger on violations of both setup time and hold time between clock and data which are on separate input channels; setup time settable from -100 ns to $+100$ ns in 200 ps increments; hold time settable from -1 ns to $+102$ ns; minimum settable window of setup time + hold time is 2 ns.

Digitizing Oscilloscope Modules Physical Characteristics

Dimensions	mm	in.
Height	262	10.3
Width	61	2.4
Depth	381	15
Weight	kg	lb.
Net	2.7	5.8
Shipping	5.8	12.8

P6243 Probe Cable Length – 1.3 m (51 in.).

P6245 Probe Cable Length – 1.3 m (51 in.).

Other Compatible Probes – P6139A, P6204, P5100, P6205, P6408, P6563A, P6701B, P6703B, AM 503S, TCP202, P6247, P6248, P6249.

Mainframes

GENERAL (TLA 714, TLA 720, TLA 7XM)

Instrument Slots –

TLA 714: Holds 4 single-wide or 2 double-wide modules.

TLA 720: Holds 10 single-wide or 5 double-wide modules.

TLA 7XM: Holds 12 single-wide or 6 double-wide modules.

PC CHARACTERISTICS (TLA 714 AND TLA 720)

Operating System – Microsoft Windows.

Processor – Pentium®.

DRAM –

TLA 714: 64 MB SDRAM (128 MB with Opt. 1S).

TLA 720: 128 MB SDRAM.

Display Memory – 2 MB.

Sound – Built-in PC speaker transducer; multi-media sound can be added via PC Card interface.

Replaceable Hard Disk Drive –

TLA 714: 6 GB (12 GB with Opt. 1s).

TLA 720: 12 GB.

A second internal fixed hard disk is available for both mainframes with TLA 7UP Opt. 04.

CD Rom – 24x, Internal.

Floppy Disk Drive – Built-in 3.5 in. 1.44 MB drive.

Year 2000 Compliant – Yes.

INTEGRAL CONTROLS (TLA 714 ONLY)

Front-Panel Display – Size: 10.4 in. diagonal. Type: Active-matrix color TFT LCD with backlight. Resolution: 800 x 600.

Colors: 16.8 M (true color).

Simultaneous Display Capability – Both the front-panel and external displays can be used simultaneously at 800 x 600 resolution.

Front-panel Knobs – Special function knobs for instrument control.

Front-panel Qwerty Keypad – Mini-QWERTY keypad and Hex keypad.

Front-panel Pointing Device – Glidepoint finger pad.

EXTERNAL PERIPHERAL INTERFACES (TLA 714 AND TLA 720)

External Display Port Type – Female DB15 SVGA connector.

External Display Resolution – Up to 1600 x 1200 non-interlaced @ 256 colors.

External Display Compatibility – DDC2B (Dynamic Display Configuration 2).

External Keyboard Port Type – PS2 mini-DIN.

External Mouse Port Type – PS2 mini-DIN.

Parallel Interface Port Type – IEEE 1284-C connector (comes standard with adapter to female DB25 connector).

Characteristics

Parallel Interface Modes – Centronics mode, EPP (Extended Parallel Port), ECP (Microsoft high-speed mode).

Serial Interface Port Type – Male DB9.

PC Card (CardBus) Slot Types – Two slots, two PC Card Type I/II or one PC Card Type III.

USB Port – Two (2).

EXTERNAL INSTRUMENTATION

INTERFACES (TLA 714 AND TLA 720)

System Trigger Output – Asserted whenever a system trigger occurs (TTL-compatible output, back-terminated into 50 Ω).

System Trigger Input – Forces a system trigger (triggers all modules) when asserted (TTL-compatible, edge-sensitive, falling-edge latched).

External Signal Output – Can be used to drive external circuitry from a module's trigger mechanism (TTL-compatible output, back-terminated into 50 Ω).

External Signal Input – Can be used to provide an external signal to arm or trigger any or all modules (TTL-compatible, level-sensitive).

P6041 External Signal Cable Length – (SMB to BNC adapter cable, two each TLA 720 only) 1.1 m (42 in.).

SYMBOLIC SUPPORT

Number of Symbols/Ranges – Unlimited (limited only by amount of virtual memory available on TLA 700).

Object File Formats Supported –

- ▶ IEEE695
- ▶ OMF 51, OMF 86, OMF 166, OMF 286, OMF 386
- ▶ COFF
- ▶ Elf/Dwarf
- ▶ Elf/Stabs
- ▶ TSF (if your software development tools do not generate output in one of the above formats, TSF or the Tektronix symbol file, a generic ASCII file format is supported. The generic ASCII file format is documented in the TLA User Manual). If a format is not listed, please contact your local Tektronix representative.

POWER

TLA 714 –

Voltage range/frequency: 90-250 VAC

@ 45-66 Hz.

100-132 VAC @ 360-440 Hz.

Input current: 6 A maximum at 90 VAC (70 A surge).

Power consumption: 600 W maximum.

TLA 720 & TLA 7XM –

Voltage range/frequency: 90-250 VAC

@ 45-66 Hz, 100-132 VAC @ 360-440 Hz.

Input current: 16.5 A maximum at 90 VAC (70 A surge).

Power consumption: 1450 W maximum.

Maximum Number of Modules & Channels per Mainframe Configuration

No TLA 7XM

Mainframe	LA*1	TLA 714 – 2 Dual/4 Single*2,3	
		PG*1	DSO*1
Max channels per module	136 ch	64 ch	4 ch
TLA 714	272	128	8
TLA 720	680	320	20

One TLA 7XM

Mainframe	LA	TLA 714 – 7 Dual/15 Single*2,3	
		PG	DSO
Max channels per module	136 ch	64 ch	4 ch
TLA 714	952	448	28
TLA 720	1,360	640	40

Two TLA 7XMs

Mainframe	LA	TLA 714 – 13 Dual/26 Single*2,3	
		PG	DSO
Max channels per module	136 ch	64 ch	4 ch
TLA 714	1,768	832	52
TLA 720	2,176	1,024	64

*1 All logic analyzer (LA), pattern generator (PG) and digitizing oscilloscope (DSO) modules are dual-wide or occupy two single-wide slots.

*2 TLA 7XM Expansion Module occupies one single-wide slot in both the TLA 714/TLA 720 mainframe and the TLA 7XM expansion mainframe.

*3 Using a TLA 7XM expansion mainframe with an existing TLA 714/TLA 720 mainframe requires Version 3.1 or higher TLA application software. TLA 720 benchtop mainframes, S/N: B019999 and lower, require TLA 7UP Option 09 TLA 720 Benchtop Mainframe Upgrade.

For configurations beyond two TLA 7XM expansion mainframes, please contact your local Tektronix account manager.

Physical Characteristics

TLA 714 Portable

Dimensions	mm	in.
Height	235	9.25
Width	432	17.00
Depth	455	17.50
Weight	kg	lb.
Net (w/o modules)	11.4	25
Shipping (typical)	25.5	56

TLA 720 Benchtop & TLA 7XM Expansion

Dimensions	mm	in.
Height	346	13.65
Width	425	16.70
Depth	673	26.5
Weight	kg	lb.
Net (w/o modules)	22.7	50
Shipping (typical)	51.8	114

Environmental

Temperature –

Operating: +5°C to +50°C.

Nonoperating: –20°C to +60°C.

Humidity –

20% to 80%.

Operating: ≤30°C; 80% relative humidity

(29°C maximum wet bulb temperature).

Nonoperating: 8% to 80% (29°C maximum wet bulb temperature).

Altitude –

Operating: –1,000 ft. to 10,000 ft. (–305 meters to 3,050 meters).

Safety – UL3111-1, CSA1010.1, EN61010-1, IEC61010-1.

TLA 714

Portable Color Mainframe.

Includes: Mouse, Keyboard, Front-panel Cover, Accessory Pouch, Two Dual-wide Panel Fillers for Empty Slots, Printer Adapter, Power Cord (North American 120 VAC, 60 Hz), Software, User Manual, Certificate of Calibration, and One-year Warranty (return to Tektronix).

TLA 720

Benchtop Color Mainframe.

Includes: Mouse, Keyboard, Five Dual-wide Panel Fillers for Empty Slots, Printer Adapter, Two P6041 SMB to BNC Adapter Cables; Power Cord (North American 120 VAC, 60 Hz), Software, User Manual, Certificate of Calibration, and One-year Warranty (return to Tektronix). Display is not included – order Opt. 1M or Opt. 2M or use any SVGA monitor.

TLA 7XM

Expansion Mainframe.

Includes: Two expansion modules, Three expansion cables, Six dual-wide panel fillers for empty slots, One single-wide panel filler for empty slot, manual, Power Cord (North American 120 VAC, 60 Hz), Statement of Compliance, and One-year Warranty (return to Tektronix).

If installing a TLA 7XM expansion mainframe into a TLA 704/TLA 711 or TLA 714/TLA 720 mainframe, please consult the TLA Family Upgrade Guide for upgrade information.

TLA 714/720 OPTIONS

Opt. 1S – 128 MB DRAM/12 GB replaceable hard disk (TLA 714 only).

Opt. 1A – Add LAN PC Card (119-6072-00).

Opt. 1K – Add LACART logic analyzer cart.

Opt. 1M – Add 17-in. monitor (119-5700-00).

Opt. 2M – Add 21-in. monitor (119-5798-00).

TLA 714/TLA 720/TLA 7XM INTERNATIONAL POWER PLUGS

Opt. A1 – Universal Euro 220 VAC; 50 Hz.

Opt. A2 – UK 240 VAC; 50 Hz.

Opt. A3 – Australian 240 VAC; 50 Hz.

Opt. A4 – North American 240 VAC; 60 Hz.

Opt. A5 – Switzerland 220 VAC; 50 Hz.

Opt. A99 – No Power Cord.

TLA 714/TLA 720/TLA 7XM FACTORY CONFIGURATION

Opt. 88 – Install modules in mainframe at factory (excludes merging of Logic Analyzer modules).

TLA 714 / TLA 720 SERVICE OPTIONS

Opt. IN – Product installation service (on-site configuration and user familiarization; excluding network integration).

Opt. R3 – Extends depot repair warranty service period to three years.

Opt. S1 – Uplifts standard one-year warranty service of mainframe and installed modules to on-site service.

Opt. S3 – Uplifts Opt. C3 and/or R3 of mainframe and installed modules to on-site service (must be ordered with Opt. C3 and/or R3).

Opt. C3 – Three years of calibration service (includes initial calibration and two annual calibrations).

Add calibration test data report.

Opt. D3 – Provides test data for each calibration (must be ordered with Opt. C3).

LOGIC ANALYZER “N & P” MODULE PROBE OPTIONS

Quantity of probes per option.

Option	TLA 7N1	TLA 7N2	TLA 7N3	TLA 7N4	TLA 7P2	TLA 7P4
1P Add P6418 Probes	2	4	6	8	4	8
2P Add P6434 Probes	1	2	3	4	2	4
3P Add P6417 Probes	2	4	6	8	4	8

TLA 7XM SERVICE OPTIONS

Opt. IN – Product installation service (on-site configuration and user familiarization; excluding network integration).

Opt. R3 – Extends depot repair warranty service period to three years.

Opt. S1 – Uplifts standard one-year warranty service of mainframe and installed modules to on-site service.

Opt. S3 – Uplifts Opt. R3 of mainframe and installed modules to on-site service (must be ordered with Opt. R3).

TLA 704/714 / TLA 711/720 / TLA 7XM OPTIONAL ACCESSORIES

Logic Analyzer Cart – LACART.

TLA 711 Rackmount Kit – Order 020-2197-00.

TLA 720/TLA 7XM Rackmount Kit – Order 020-2221-00.

TLA 704/714 Wheeled Transport Case – Order 016-1522-00.

TLA 711/720/TLA 7XM Wheeled Transport Case – Order 016-1651-00.

17 in. Monitor Transport Case – Order 016-1653-00.

21 in. Monitor Transport Case – Order 016-1652-00.

83 Key Notebook Keyboard, PS2 – Compatible – Order 118-9402-00.

TLA 7QS – TLA Family Training Package. (TLA 700 configuration required: 102 channel logic analyzer module (required) plus 2 channel digitizing oscilloscope module (optional)).

Opt. A1 – Universal Euro.

Opt. A2 – United Kingdom.

Opt. A6 – Japan.

TLA 7QS Technical Reference Support Kit – Order 020-2211-02.

TLA 700 SERIES MANUALS

TLA Family User Manual – Order 071-0729-00 (for Version 3.2 TLA application software).

TLA 7QS Quickstart Training Manual – Order 071-9717-05.

TLA 700 SERIES SERVICE MANUALS AND TEST FIXTURES

TLA 704 Service Manual – Order 070-9777-00.

TLA 714 Service Manual – Order 071-0267-00.

TLA 711 Chassis Service Manual – Order 070-9773-00.

TLA 720 Color Benchtop Chassis and TLA 7XM Expansion Chassis Service Manual – Order 071-0699-00.

TLA 711 Controller Service Manual – Order 070-9778-00.

TLA 720 Controller Service Manual – Order 071-0269-01.

TLA 7XM Expansion Module Service Manual – Order 071-0674-00.

TLA Family Performance Verification and Adjustment Technical Reference Manual (Requires Logic Analyzer Adjustment Fixture) – Order 070-9776-04.

TLA Logic Analyzer Adjustment Fixture (includes AC adapter; requires local power cord) – Order 671-3599-00.

TLA 7Lx/7Mx Logic Analyzer Modules Service Manual – Order 070-9779-00.

TLA 7Nx/7Px Logic Analyzer Modules Service Manual – Order 071-0266-01.

TLA 7PG Pattern Generator Module Service Manual – Order 071-0714-00.

TLA 7Dx/7Ex DSO Modules Service Manual – Order 070-9780-02.

TLA 700 SERIES MAINFRAME UPGRADES

You can upgrade the operating system, TLA application software, increase DRAM and hard disk, add existing modules as well as other new capabilities to your existing TLA 700 mainframe.

Please refer to TLA Family Upgrade Guide for further details.

LOGIC ANALYZER MODULES

Includes: Probe retainer bracket, Probe Manual, User Manual, Certificate of Calibration, One-year Warranty (return to Tektronix), and your choice of probes.

TLA 7N1 – 34 channel Logic Analyzer module, 2 GHz timing, 100 MHz state, 64 K depth (must select one probe option below). Options for up to 4 M depth and/or 200 MHz state.

TLA 7N2 – 68 channel Logic Analyzer module, 2 GHz timing, 100 MHz state, 64 K depth (must select one probe option below). Options for up to 4 M depth and/or 200 MHz state.

TLA 7N3 – 102 channel Logic Analyzer module, 2 GHz timing, 100 MHz state, 64 K depth (must select one probe option below). Options for up to 4 M depth and/or 200 MHz state.

TLA 7N4 – 136 channel Logic Analyzer module, 2 GHz timing, 100 MHz state, 64 K depth (must select one probe option below). Options for up to 4 M depth and/or 200 MHz state.

TLA 7P2 – 68 channel Logic Analyzer module, 2 GHz timing, 100 MHz state, 16 M depth (must select one probe option below). Options for up to 200 MHz state.

TLA 7P4 – 136 channel Logic Analyzer module, 2 GHz timing, 100 MHz state, 16 M depth (must select one probe option below). Options for up to 200 MHz state.

Opt. 1P – Add P6418 17 channel general-purpose probes (each includes two 8 channel leadsets, one 1 channel leadset, 20 SMT KlipChip™ grabber tips).

Opt. 2P – Add P6434 34 channel high-density probe(s).

Opt. 3P – Add P6417 17 channel general-purpose probes (each includes two 8 channel leadsets, one 1 channel leadset, 20 SMT KlipChip grabber tips).

LOGIC ANALYZER "N" MODULE OPTIONS

(Base configuration is 64 K depth @ 100 MHz state)

- 1S** – Increase to 256 K depth @ 100 MHz state.
- 2S** – Increase to 1 M depth @ 100 MHz state.
- 3S** – Increase to 4 M depth @ 100 MHz state.
- 4S** – Increase to 64 K depth @ 200 MHz state.
- 5S** – Increase to 256 K depth @ 200 MHz state.
- 6S** – Increase to 1 M depth @ 200 MHz state.
- 7S** – Increase to 4 M depth @ 200 MHz state.

LOGIC ANALYZER "P" MODULE OPTIONS

(Base configuration is 16 M depth @ 100 MHz state)

- 1S** – Increase to 16 M depth @ 200 MHz state.

TLA 700 SERIES MODULE UPGRADES

You can increase the memory depth and state speed of most existing TLA 700 Series logic analyzer modules. You can also install a TLA 7Nx/Px logic analyzer module into an existing TLA 704/711 or TLA 714/720 mainframe. Please refer to the TLA Family Upgrade Guide for further details.

LOGIC ANALYZER MODULE SERVICE OPTIONS

- Opt. IN** – Product installation service (on-site configuration and user familiarization, excluding network integration).
- Opt. R3** – Extends depot repair warranty service period to three years.
- Opt. C3** – Three years of calibration service (includes initial certification and two annual calibrations).
- Opt. D1** – Add calibration test data report.
- Opt. D3** – Provide test data for each calibration (must be ordered with Opt. C3).

LOGIC ANALYZER PROBE SELECTION GUIDELINES

For the TLA 7Nx/Px logic analyzer modules, you have your choice of three probe options:

P6418 (TLA 7Nx/Px Option 1P) – The P6418 (application not pictured) is a 17 channel general-purpose probe with leadsets and grabber tips for use with: 1) probing individual test points within your target system, either directly or with a test clip, or 2) direct connection to legacy TLA family processor/bus support probe adapters with 8 channel probe connectors. The P6418 works with a wide-range of industry-standard probing accessories for flexible attachment to your target system. This probe is recommended for most general-purpose applications.

P6417 (TLA 7Nx/Px Option 3P) – The P6417 (application shown below) is a 17 channel general-purpose probe that is similar to the P6418 with the additional capability that it allows you to separate the 8 channel podlet groups into individual channels for both maximum electrical performance and maximum distance between adjacent channels. This probe is recommended for those general-purpose applications that require maximum flexibility.

P6434 (TLA 7Nx/Px Option 2P) – The P6434 (application shown below) is a lightweight probe with quick connect/disconnect and a positive latching mechanism to ensure a secure, reliable connection. It is for use with: 1) applications where you have designed in the AMP® Mictor® high-density connectors into your target system, or 2) direct connection to newer TLA family processor/bus support probe adapters with AMP Mictor 34 channel probe connectors. An optional low-profile adapter for low-clearance applications is also available. This probe is recommended for all high-density applications.

LOGIC ANALYZER MODULE PROBES AND ACCESSORIES

17 channel general-purpose Probe and Accessories for TLA 7Lx/TLA 7Mx, TLA 7Nx/TLA 7Px Logic Analyzer Modules – Order P6417.

17 channel general-purpose Probe and Accessories for TLA 7Lx/TLA 7Mx, TLA 7Nx/TLA 7Px Logic Analyzer Modules – Order P6418.

PATTERN GENERATOR MODULE

TLA 7PG2 – 64 channel Pattern Generator Module, 134 MHz data rate, 256 K depth (please select probe option below).

Includes: Four probe cables, User Manual, Certificate of Calibration and one year warranty (return to Tektronix).

- Opt. 1M** – Increase to 1 M depth.
- Opt. 1P** – Add four P6470 TTL/CMOS probes (each includes two 8 channel leadsets and one 5 channel leadset).
- Opt. 2P** – Add four P6471 ECL probes (each includes two 8 channel leadsets and one 5 channel leadset).
- Opt. 1C** – Add 168 SMT KlipChip grabber tips.

TLA700 SERIES PATTERN GENERATOR MODULE(S) UPGRADES

You can increase the memory depth of most existing TLA 700 Series pattern generator modules. You can also install a TLA 7PG2 pattern generator module into and existing TLA 704/711 or TLA 714/720 mainframe. Please refer to the TLA Family Upgrade Guide for further details.

PATTERN GENERATOR MODULE SERVICE OPTIONS

- Opt. IN** – Product installation service (on-site configuration and user familiarization, excluding network integration).
- Opt. R3** – Extends depot repair warranty service period to three years.
- Opt. C3** – Three years of calibration service (includes initial certification and two annual calibrations).
- Opt. D1** – Add calibration test data report.
- Opt. D3** – Provide test data for each calibration (must be ordered with Opt. C3).

16 channel TTL/CMOS Probe and Accessories for TLA 7PG2 Pattern Generator Module – Order P6470.

Part Number	Description
116-0937-00	16 channel TTL/CMOS probe
012-1581-00	2 each – 8 channel leadsets
012-1580-00	1 each – 5 channel leadset
012-1570-00	(optional – std with TLA 7PG2 module) Probe Cable

16 channel ECL Probe and Accessories for TLA 7PG2 Pattern Generator Module – Order P6471.

Part Number	Description
116-0938-00	16 channel ECL probe
012-1581-00	2 each – 8 channel leadsets
012-1580-00	1 each – 5 channel leadset
012-1570-00	(optional – std with TLA 7PG2 module) Probe Cable

DIGITIZING OSCILLOSCOPE MODULES

Includes: Probes, User Manual, Certificate of Calibration, and One-year Warranty (return to Tektronix).

TLA 7D1 – 2 channel DSO module, 500 MHz bandwidth, 2.5 GS/s sample rate, 15 K depth (includes two P6243 1.0 GHz active FET probes, probe calibration adapter, and manual).

TLA 7D2 – 4 channel DSO module, 500 MHz bandwidth, 2.5 GS/s sample rate, 15 K depth (includes four P6243 1.0 GHz active FET probes, probe calibration adapter, and manual).

TLA 7E1 – 2 channel DSO module, 1 GHz bandwidth, 5 GS/s sample rate, 15 K depth (includes two P6245 1.5 GHz active FET probes, probe calibration adapter, and manual).

TLA 7E2 – 4 channel DSO module, 1 GHz bandwidth, 5 GS/s sample rate, 15 K depth (includes four P6245 1.5 GHz active FET probes, probe calibration adapter, and manual).

TLA700 SERIES DSO MODULE UPGRADES

You can install a TLA 7Dx/Ex digitizing oscilloscope module into an existing TLA 704/711 or TLA 714/720 mainframe. Please refer to the TLA Family Upgrade Guide for further details.

DSO MODULE SERVICE OPTIONS

- Opt. IN** – Product installation service (on-site configuration and user familiarization, excluding network integration).
- Opt. R3** – Extends depot repair warranty service period to three years.
- Opt. C3** – Three years of calibration service (includes initial certification and two annual calibrations).
- Opt. D1** – Add calibration test data report.
- Opt. D3** – Provide test data for each calibration (must be ordered with Opt. C3).

For further information, contact Tektronix:



Worldwide Web: for the most up-to-date product information visit our web site at: www.tektronix.com/Measurement/logic_analyzers/

ASEAN Countries (65) 356-3900; Australia & New Zealand 61 (2) 9888-0100; Austria, Central Eastern Europe, Greece, Turkey, Malta, & Cyprus +43 2236 8092 0; Belgium +32 (2) 715 89 70; Brazil and South America 55 (11) 3741-8360; Canada 1 (800) 661-5625; Denmark +45 (44) 850 700; Finland +358 (9) 4783 400; France & North Africa +33 1 69 86 81 81; Germany + 49 (221) 94 77 400; Hong Kong (852) 2585-6688; India (91) 80-2275577; Italy +39 (2) 25086 501; Japan (Sony/Tektronix Corporation) 81 (3) 3448-3111; Mexico, Central America, & Caribbean 52 (5) 666-6333; The Netherlands +31 23 56 95555; Norway +47 22 07 07 00; People's Republic of China 86 (10) 6235 1230; Republic of Korea 82 (2) 528-5299; South Africa (27 11)651-5222; Spain & Portugal +34 91 372 6000; Sweden +46 8 477 65 00; Switzerland +41 (41) 729 36 40; Taiwan 886 (2) 2722-9622; United Kingdom & Eire +44 (0)1344 392000; USA 1 (800) 426-2200.



From other areas, contact: Tektronix, Inc. Export Sales, P.O. Box 500, M/S 50-255, Beaverton, Oregon 97077-0001, USA 1 (503) 627-6877.

Copyright © 2000, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

05/00 HB/XBS 52W-11144-5

Tektronix