

# Keysight N5264B Measurement Receiver

Technical  
Specifications  
and Data Sheet

## Documentation Warranty

THE MATERIAL CONTAINED IN THIS DOCUMENT IS PROVIDED "AS IS," AND IS SUBJECT TO BEING CHANGED, WITHOUT NOTICE, IN FUTURE EDITIONS. FURTHER, TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, KEYSIGHT DISCLAIMS ALL WARRANTIES, EITHER EXPRESS OR IMPLIED WITH REGARD TO THIS MANUAL AND ANY INFORMATION CONTAINED HEREIN, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. KEYSIGHT SHALL NOT BE LIABLE FOR ERRORS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH THE FURNISHING, USE, OR PERFORMANCE OF THIS DOCUMENT OR ANY INFORMATION CONTAINED HEREIN. SHOULD KEYSIGHT AND THE USER HAVE A SEPARATE WRITTEN AGREEMENT WITH WARRANTY TERMS COVERING THE MATERIAL IN THIS DOCUMENT THAT CONFLICT WITH THESE TERMS, THE WARRANTY TERMS IN THE SEPARATE AGREEMENT WILL CONTROL.

## U.S. Government Rights

U.S. Government Rights. The Software is "commercial computer software," as defined by Federal Acquisition Regulation ("FAR") 2.101. Pursuant to FAR 12.212 and 27.405-3 and Department of Defense FAR Supplement ("DFARS") 227.7202, the U.S. government acquires commercial computer software under the same terms by which the software is customarily provided to the public. Accordingly, Keysight provides the Software to U.S. government customers under its standard commercial license, which is embodied in its End User License Agreement (EULA), a copy of which can be found at <http://www.keysight.com/find/sweula>. The license set forth in the EULA represents the exclusive authority by which the U.S. government may use, modify, distribute, or disclose the Software. The EULA and the license set forth therein, does not require or permit, among other things, that Keysight: (1) Furnish technical information related to commercial computer software or commercial computer software documentation that is not customarily provided to the public; or (2) Relinquish to, or otherwise provide, the government rights in excess of these rights customarily provided to the public to use, modify, reproduce, release, perform, display, or disclose commercial computer software or commercial computer software documentation. No additional government requirements beyond those set forth in the EULA shall apply, except to the extent that those terms, rights, or licenses are explicitly required from all providers of commercial computer software pursuant to the FAR and the DFARS and are set forth specifically in writing elsewhere in the EULA. Keysight shall be under no obligation to update, revise or otherwise modify the Software. With respect to any technical data as defined by FAR 2.101, pursuant to FAR 12.211 and 27.404.2 and DFARS 227.7102, the U.S. government acquires no greater than Limited Rights as defined in FAR 27.401 or DFAR 227.7103-5 (c), as applicable in any technical data.

## Contents

Table 1. Key Specifications .....	4
Table 2. Measurement Throughput Summary .....	4
Table 3. Rear Panel Information .....	8
Table 4. Front Panel Information .....	14
Table 5. Analyzer Dimensions and Weight .....	15

## Definitions

All specifications and characteristics apply over a  $25\text{ }^{\circ}\text{C} \pm 5\text{ }^{\circ}\text{C}$  range (unless otherwise stated) and 90 minutes after the instrument has been turned on.

**Specification (spec.):** Warranted performance. Specifications include guardbands to account for the expected statistical performance distribution, measurement uncertainties, and changes in performance due to environmental conditions.

**Characteristic (char.):** A performance parameter that the product is expected to meet before it leaves the factory, but that is not verified in the field and is not covered by the product warranty. A characteristic includes the same guardbands as a specification.

**Typical (typ.):** Expected performance of an average unit which does not include guardbands. It is not covered by the product warranty.

**Nominal (nom.):** A general, descriptive term that does not imply a level of performance. It is not covered by the product warranty.

**Calibration:** The process of measuring known standards to characterize a network analyzer's systematic (repeatable) errors.

**Corrected (residual):** Indicates performance after error correction (calibration). It is determined by the quality of calibration standards and how well "known" they are, plus system repeatability, stability, and noise.

**Uncorrected (raw):** Indicates instrument performance without error correction. The uncorrected performance affects the stability of a calibration.

**Standard:** When referring to the analyzer, this includes no options unless noted otherwise.

## Table 1. Key Specifications

Description	Specifications
Measurement Speed (max) points/sec @ 600 KHz IFBW, CW frequency	400,000 points/sec <sup>1</sup>
Receiver Inputs	5 (simultaneously)
Measurement Receivers	5 (simultaneously)
Data Buffer Size	4 billion bytes
Data Buffer size (max. points for single cut)	500 million points <sup>2</sup>
IF Bandwidth	1 Hz to 5 MHz
Frequency Source Control Interface	TLL hand shake
Trigger In / Out	Three pairs
Host Computer Interface	Ethernet, USB and GPIB
Security	Hard drive removable

<sup>1</sup> Fast CW mode - no point triggering.

<sup>2</sup> For single parameter; two parameters are 250 million points each.

## Table 2. Measurement Throughput Summary

Typical Cycle Time<sup>1,2</sup> (ms) for Measurement Completion

Description	Typical Performance (time/point in millisecond)			
Number of Points	CW 10 GHz (no band crossings), 801 points			
Trigger Mode	Hardware			
IF Bandwidth	600 kHz	100 kHz	10 kHz	1 kHz
RF = MXG, N5183A opt. UNZ, Fast switching LO = MXG, N5183A opt. UNZ, Fast switching	0.070	0.075	0.185	1.00
RF = MXG, N5183A opt. UNZ, Fast switching LO = N5264B opt. 108 <sup>3</sup>	0.070	0.075	0.185	1.00
RF = MXG, N5183A opt. UNZ, Fast switching LO = PSG	0.350	0.350	0.450	0.250
RF = MXG, N5183A opt. UNZ, Fast switching LO = 83623B	0.900	0.900	1.00	1.800
RF = UXG, N5193A opt. SS1, 1 μs switching speed LO = UXG, N5193A opt. SS1, 1 μs switching speed	.020	.027	.140	.940

Description	Typical Performance (time/point in millisecond)		
	Standard		
Number of Points	801	1601	
Trigger Mode	Hardware		Sensitivity(dBm) <sup>4</sup>
<b>Start 2 GHz, Stop 18 GHz, 1 MHz IF bandwidth (with band crossings)</b>			
RF = MXG, N5183A opt. UNZ, Fast switching LO = MXG, N5183A opt. UNZ, Fast switching	0.580	0.580	-90.5 dBm, 2 – 3 GHz - 94.5 dBm, 3 – 12.5 GHz - 83 dBm, 12.5 – 18 GHz
RF = MXG, N5183A opt. UNZ, Fast switching LO = N5264B opt. 108 <sup>3</sup>	0.580	0.580	-85.5 dBm, 2 – 3 GHz - 90.5 dBm, 3 – 12.5 GHz - 81 dBm, 12.5 – 18 GHz
RF = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed LO = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed	0.039	0.034	-90.5 dBm, 2 – 3 GHz - 94.5 dBm, 3 – 12.5 GHz - 83 dBm, 12.5 – 18 GHz
<b>Start 2 GHz, Stop 18 GHz, 600 kHz IF bandwidth (with band crossings)</b>			
RF = MXG, N5183A opt. UNZ, Fast switching LO = MXG, N5183A opt. UNZ, Fast switching	0.580	0.580	-92.5 dBm, 2 – 3 GHz - 96.5 dBm, 3 – 12.5 GHz - 85 dBm, 12.5 – 18 GHz
RF = MXG, N5183A opt. UNZ, Fast switching LO = N5264B opt. 108 <sup>3</sup>	0.580	0.580	-85.5 dBm, 2 – 3 GHz - 92.5 dBm, 3 – 12.5 GHz - 83 dBm, 12.5 – 18 GHz
RF = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed LO = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed	0.045	0.039	-92.5 dBm, 2 – 3 GHz - 96.5 dBm, 3 – 12.5 GHz - 85 dBm, 12.5 – 18 GHz
<b>Start 2 GHz, Stop 18 GHz, 10 kHz IF bandwidth (with band crossings)</b>			
RF = MXG, N5183A opt. UNZ, Fast switching LO = MXG, N5183A opt. UNZ, Fast switching	0.730	0.730	-110.5 dBm, 2 – 3 GHz - 114.5 dBm, 3 – 12.5 GHz - 103 dBm, 12.5 – 18 GHz
RF = MXG, N5183A opt. UNZ, Fast switching LO = N5264B opt. 108 <sup>3</sup>	0.730	0.730	-103.5 dBm, 2 – 3 GHz - 110.5 dBm, 3 – 12.5 GHz - 101 dBm, 12.5 – 18 GHz
RF = MXG, N5183A opt. UNZ, Fast switching LO = PSG E8267D opt. 520, UNX	9.50	9.50	-110.25 dBm, 2 – 3 GHz - 112.50 dBm, 3 – 12.5 GHz - 96.50 dBm, 12.5 – 18 GHz
RF = MXG, N5183A opt. UNZ, Fast switching LO = 83623B	7.80	--	-108.5 dBm, 2 – 3 GHz - 113.0 dBm, 3 – 12.5 GHz - 96.0 dBm, 12.5 – 18 GHz
RF = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed LO = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed	0.170	0.167	-110.5 dBm, 2 – 3 GHz - 114.5 dBm, 3 – 12.5 GHz - 103 dBm, 12.5 – 18 GHz

<b>Start 2 GHz, Stop 18 GHz, 1 kHz IF bandwidth (with band crossings)</b>			
RF = MXG, N5183A opt. UNZ, Fast switching	1.5	1.5	-120.5 dBm, 2 – 3 GHz
LO = MXG, N5183A opt. UNZ, Fast switching			- 124.5 dBm, 3 –12.5 GHz - 113 dBm, 12.5 – 18 GHz
RF = MXG, N5183A opt. UNZ, Fast switching	1.5	1.5	-113.5 dBm, 2 – 3 GHz
LO = N5264B opt. 108 <sup>3</sup>			- 120.5 dBm, 3 –12.5 GHz - 111 dBm, 12.5 – 18 GHz
RF = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed	0.970	0.970	-120.5 dBm, 2 – 3 GHz
LO = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed			- 124.5 dBm, 3 –12.5 GHz - 113 dBm, 12.5 – 18 GHz
<b>Start 2 GHz, Stop 18 GHz, 500 Hz IF bandwidth (with band crossings)</b>			
RF = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed	1.85	1.85	-120.5 dBm, 2 – 3 GHz
LO = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed			- 124.5 dBm, 3 –12.5 GHz - 113 dBm, 12.5 – 18 GHz

<b>Option 118 Fast-CW mode (CW frequency)</b>		
	<b>Number of Points per Second (#pt/Sec)</b>	<b>External Trigger</b>
C.W, 7.0 GHz, $\geq$ 1 MHz IF bandwidth	--	400,000
C.W, 7.0 GHz, 600 KHz IF bandwidth	Up to 400,000	240,000
C.W, 7.0 GHz, 10 KHz IF bandwidth	Up to 8,200	7,000
C.W, 7.0 GHz, 1 KHz IF bandwidth	Up to 1,000	1,000

Time/Point (ms)

<b>Description</b>	<b>Typical Performance</b>					
<b>Start 2 GHz, Stop 18 GHz, 801 points (with band crossings), hardware trigger</b>						
<b>IF Bandwidth</b>	<b>1 MHz</b>	<b>600 kHz</b>	<b>100 kHz</b>	<b>10 kHz</b>	<b>1 kHz</b>	<b>500 Hz</b>
RF = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed	.032	.035	.047	.165	.965	1.85
LO = UXG, N5193A opt. SS1, 1 $\mu$ s switching speed						

## Data Transfer Time (ms)

Description	Typical Performance			
	Number of Points			
	201	401	1601	16,001
<b>SCPI over GPIB</b>				
Program executed on external PC <sup>5</sup>				
32-bit floating point	5.6	10.5	39.9	400
64-bit floating point	10.5	20.3	79.2	788
ASCII	46	92.5	370	3702
<b>SCPI over SICL/LAN or TCP/IP Socket</b>				
Program executed in the analyzer				
32-bit floating point	0.18	0.21	0.5	3.6
64-bit floating point	0.22	0.28	0.62	5.3
ASCII	6.3	12.3	47.3	470
<b>COM<sup>6</sup></b>				
Program executed in the analyzer				
32-bit floating point	<0.15	0.15	0.2	0.7
Variant type	0.75	1.2	4.5	50
<b>DCOM over LAN<sup>6</sup></b>				
Program executed on external PC				
32-bit floating point	<1.0	1.2	2.1	13
Variant type	2.7	4.5	15	150

<sup>1</sup> Includes sweep time, retrace time and band-crossing time. Analyzer display turned on. Minus 21 ms from total time for display off with DISPLAY:ENABLE OFF. Data for two traces (A & B receiver) per measurement.

<sup>2</sup> After first complete sweep.

<sup>3</sup> When configuring the N5264B Option 108 as the LO source, you may improve system measurement sensitivity by using a method of AM noise suppression.

<sup>4</sup> Performance Characteristics when connected with 85309A and 85320A/B mixers - system noise floor + conversion gain.

<sup>5</sup> Measured when using the SCPI command DISPlay: VISible OFF.

<sup>6</sup> Values are for real and imaginary pairs, with the analyzer display off.

### Table 3. Rear Panel Information

External IF Inputs	
Description	Typical Performance
Function	Allows use of external IF signals from remote mixers or frequency converters
Connectors	SMA (female); A, B, C, D, R
Input Frequency	7.438017 MHz (See IF Input Frequencies below.)
Input Impedance	50 $\Omega$
RF Damage Level	+23 dBm
DC Damage Level	1 VDC
0.1 dB Compression Point	-9.0 dBm
Compression @ -10 dBm	
Magnitude	0.03 dB
Phase	0.23°
Noise Floor	
10 Hz IF BW	-143 dBm
10KHz IF BW	-113 dBm
Crosstalk	-134 dB <sup>1</sup>
Dynamic Range @ 10 Hz	134 dB @ 0.1dB compression to noise floor
<b>Dynamic Accuracy</b>	
-40 dBm reference, over range set by compression and noise floor @ IF Frequencies	
-10 dBm	0.037 dB
-20 dBm	0.024 dB
-30 dBm	0.016 dB
-40 dBm	0.010 dB
-50 dBm	0.013 dB
-60 dBm	0.021 dB
-70 dBm	0.032 dB



## IF Input Frequencies

The IF Input frequencies are different depending on the DSP Version.

### With DSP Version 4:

- RF or Transmitting frequency < 53 MHz: IF = 2.535211 MHz [ $3 \times (60e6 / 71)$ ]
- RF or Transmitting frequency  $\geq$  53 MHz: IF = 7.605634 MHz [ $9 \times (60e6 / 71)$ ]

With DSP Version 5, the IF frequency is dependent on the RF or Transmitting frequency AND the current IFBW setting:

- All RF or Transmitting frequency; IF Bandwidth  $\geq$  1MHz

IFBW Setting	IF Frequency
1 MHz	7.692 MHz
1.5 MHz	7.368 MHz
2 MHz	8.450 MHz
3 MHz	8.163 MHz
5 MHz	6.897 MHz
7 MHz	10.53 MHz
10 MHz	15.38 MHz
15 MHz	22.22 MHz

- IF Bandwidth  $\leq$  600 kHz:
  - RF or Transmitting frequency < 53 MHz; IF = 2.479339 MHz [ $(3 \times (100e6 / 121))$ ]
  - RF or Transmitting frequency  $\geq$  53 MHz; IF = 7.438017 MHz [ $(9 \times (100e6 / 121))$ ]

### Manually change the IF frequency

The IF frequency can be changed to any value between +14.9999 MHz and -14.9999 MHz using SENS:IF:FREQ (SCPI) or IFFrequency (COM) commands.

- With DSP Version 4 - 34 and above, min and max IF frequencies up to +/- 20.1 MHz are available.
- With DSP Version 5, min and max IF frequencies up to +/- 38 MHz are available.
- Performance is degraded drastically above +/- 14.9999 MHz.

<b>External IF Inputs (Cont.)</b>	
<b>Description</b>	<b>Typical Performance</b>
<b>Dynamic Accuracy (Cont.)</b>	
-40 dBm reference, over range set by compression and noise floor @ IF Frequencies	
-80 dBm	0.041 dB
-90 dBm	0.049 dB
-100 dBm	0.057 dB
-110 dBm	0.072 dB
-120 dBm	0.188 dB
<b>LO output 2 (Option 108)</b>	
<b>Description</b>	<b>Specification</b>
Frequency Stability	+/- 0.05 ppm, -10 to 70C, +/- 0.1ppm/yr max
Frequency Accuracy	+/- 1 ppm
<b>Description</b>	<b>Typical Performance</b>
Frequency Range	10 MHz to 26.5 GHz
<b>Frequency Switching Speed<sup>3</sup></b>	< 100 microsecond/point
Frequency Resolution	1 Hz
Power Flatness	+/- 1.0 dB
Power Output	+10 dBm
<b>2<sup>nd</sup> Harmonics<sup>4</sup></b>	
20 MHz to 2.0 GHz	-23 dBc
2.0 GHz to 5.0 GHz	-28 dBc
5.0 GHz to 23.0 GHz	-35 dBc
23.0 GHz to 26.5 GHz	-27 dBc

<b>LO output 2 (Option 108)</b>				
<b>Description</b>	<b>Typical Performance</b>			
<b>3<sup>rd</sup> Harmonics<sup>3</sup></b>				
30 MHz to 8.0 GHz	-32 dBc			
8.0 GHz to 15.0 GHz	-38 dBc			
15.0 GHz to 26.5.0 GHz	-48 dBc			
<b>Phase Noise</b>				
	<b>1 KHz Offset</b>	<b>10 KHz Offset</b>	<b>100 KHz Offset</b>	<b>1 MHz Offset</b>
10 MHz to 500 MHz	-80 dBc/Hz	-85 dBc/Hz	-76 dBc/Hz	-113 dBc/Hz
500 MHz to 1 GHz	-90 dBc/Hz	-110 dBc/Hz	-106 dBc/Hz	-115 dBc/Hz
1 GHz to 2 GHz	-85 dBc/Hz	-105 dBc/Hz	-101 dBc/Hz	-110 dBc/Hz
2 GHz to 4 GHz	-80 dBc/Hz	-100 dBc/Hz	-96 dBc/Hz	-105 dBc/Hz
4 GHz to 8 GHz	-74 dBc/Hz	-94 dBc/Hz	-90 dBc/Hz	-99 dBc/Hz
8 GHz to 16 GHz	-68 dBc/Hz	-88 dBc/Hz	-84 dBc/Hz	-93 dBc/Hz
16 GHz to 26.5 GHz	-62 dBc/Hz	-82 dBc/Hz	-78 dBc/Hz	-87 dBc/Hz
<b>10 MHz Reference</b>				
<b>10 MHz Reference In</b>				
Connector	BNC, female			
Input Frequency	10 MHz ± 10 ppm, typical			
Input Level	-15 dBm to +20 dBm, typical			
Input Impedance	200 Ω, nom.			
<b>10 MHz Reference Out</b>				
Connector	BNC, female			
Output Frequency	10 MHz ± 1 ppm			
Signal Type	Sine Wave, typical			
Output Level	+10 dBm ± 4 dB into 50 Ω			
Output Impedance	50 Ω, nominal			
Harmonics	< -40 dBc, typical			

**External Monitor Information**

Description	Typical Performance
<b>VGA Video Output</b>	
Connector	15-pin mini D-Sub; Drives VGA compatible monitors
<b>Devices Supported:</b>	<b>Resolutions:</b>
Flat Panel (TFT)	1024 X 768, 800 X 600, 640 X 480
Flat Panel (DSTN)	800 X 600, 640 X 480
CRT Monitor	1280 X 1024, 1024 X 768, 800 X 600, 640 X 480
--	Simultaneous operation of the internal and external displays is allowed, but with 640 X 480 resolution only. If you change resolution, you can only view the external display (internal display will "white out").
Test Set IO	25-pin D-Sub connector, available for external test set control.
Power IO	9-pin D-Sub, female; analog and digital IO
Handler IO	36-pin parallel I/O port; all input/output signals are default set to negative logic; can be reset to positive logic via GPIB command.

**Trigger Information**

Description	Typical Performance
<b>Trigger In/Meas Trigger</b>	
Nominal Input Impedance	5K Ohms
Minimum Pulse Width	1 us
DC Damage Level	5.5 volts
Drive Voltage	TTL (0, +5.0) Volts

**Trigger Information (Cont.)**

Description	Typical Performance
<b>Trigger out/Meas Trigger Ready</b>	
Nominal Input Impedance	5K Ohm
Pulse Width	= Data acquisition
Polarity	Selectable with sweep or point mode
Drive Voltage	TTL (0, +5.0) Volts
Trigger Inputs/Outputs (Aux. 1 & 2)	BNC(f), TTL/CMOS compatible
GPIB (two ports - dedicated controller and dedicated talker/listener)	24-pin D-sub (Type D-24), female; compatible with IEEE-488.
Parallel Port (LPT1)	25-pin D-Sub miniature connector, female; provides connection to printers or any other parallel port peripherals
Serial Port (COM 1)	9-pin D-Sub, male; compatible with RS-232
USB Port	Four ports on front panel (all Host) and five ports (four hosts and one Device) on rear panel. Type A configuration (eight hosts) and Type B configuration (one Device), USB 2.0 compatible.
LAN	10/100BaseT Ethernet, 8-pin configuration; auto selects between the two data rates

**Line Power**

Description	Typical Performance
Power supply is auto switching	
Frequency, Voltage	50/60 Hz for 100 240 VAC
Max	450 watts

<sup>1</sup> Measurement conditions: normalized to -10 dBm, 10 Hz IFBW, averaging factor of 8.

<sup>2</sup> Absolute LO frequency is Front Panel set frequency plus 1 IF.

<sup>3</sup> No band crossings; IFBW  $\geq$  100 kHz with 801 measurement points.

<sup>4</sup> Listed frequency is the harmonic frequency setting entered with front panel (frequency setting entered with front panel plus {IF frequency} \* {harmonic number}) at typical power.

**Table 4. Front Panel Information**

Description	Typical Performance
<b>USB 2.0 Ports</b>	
Number of ports	4
Standard	Compatible with USB 2.0
Connector	USB Type-A female
<b>Display</b>	
Size	31 cm (12.1 in) diagonal color active matrix LCD; 1280 (horizontal) X 800 (vertical) resolution
Refresh Rate	Vertical 60 Hz; Horizontal 49.31 kHz
Pixels	Any of the following would cause a display to be considered faulty: <ul style="list-style-type: none"> <li>• A complete row or column consists of “stuck” or “dark” pixels.</li> <li>• More than six “stuck on” pixels (but not more than three green) or more than 0.002% of the total pixels are within the LCD specifications.</li> <li>• More than twelve “dark” pixels (but no more than seven of the same color) or more than 0.004% of the total pixels are within the LCD specifications.</li> <li>• Two or more consecutive “stuck on” pixels or three or more consecutive “dark” pixel (but no more than one set of two consecutive dark pixels).</li> <li>• “Stuck on” pixels or more than two “dark” pixels less than 6.5 mm apart (excluding consecutive pixels).</li> </ul>
<b>Display Range</b>	
Magnitude	+/-2500 dB (at 500 dB/div), max
Phase	+/-2500° (at 500 °/div), max
Polar	10 pUnits, min 10,000 Units, max
<b>Display Resolution</b>	
Magnitude	0.001 dB/div, min
Phase	0.01°/div, min
<b>Marker Resolution</b>	
Magnitude	0.001 dB, min
Phase	0.01°, min
Polar	10 pUnit, min


## Table 5. Analyzer Dimensions and Weight

Cabinet Dimensions	Height	Width	Depth
Excluding front and rear panel hardware and feet	267 mm 10.5 in	426 mm 16.75 in	533 mm 20.97 in
Excluding front and rear panel hardware and feet. Including rack-mount flanges.	266 mm 10.5 in EIA RU <sup>1</sup> = 6	426 mm 16.75 in	558 mm 21.95 in
As shipped - including front panel connectors, rear panel bumpers, and feet.	280 mm 11.0 in	435 mm 17.1 in	558 mm 21.95 in
As shipped including rack-mount flanges	280 mm 11.0 in	483 mm 19.00 in	558 mm 21.95 in
Weight			
	Standard	Option 108	--
Net	21 kg (45 lb), nominal	22 kg (48 lb), nominal	--
Shipping	37 kg (82 lb), nominal	38 kg (85 lb), nominal	--

<sup>1</sup> Feet removed from the N5264B.

**NOTE**

For Regulatory and Environmental information, refer to the PNA Series Installation and Quick Start Guide, located online at <http://literature.cdn.keysight.com/litweb/pdf/E8356-90001.pdf>.





This information is subject to change without notice.

© Keysight Technologies 2017-2018

Print Date: April 25, 2018



N5264-90030

[www.keysight.com](http://www.keysight.com)