

5 Essential Hints to Improve Millimeter-wave Network Analysis





Essential Hints to Improve Millimeter-wave Network Analysis

2,5 ×

Ensure accurate, repeatable results

......

Gain confidence with an off-the-shelf solution

Assembling a "roll your own" millimeter-wave network analyzer can be challenging and time-consuming. Worse, there are no guaranteed specifications for stability or accuracy.

The better alternative is a preconfigured solution that includes a two- or four-port network analyzer along with the necessary millimeter-wave cabling, frequency extenders and test-set controller. With the N5290/91A solutions, you can select either a PNA or PNA-X network analyzer with maximum frequency of 26.5 GHz or 67 GHz. Our configuration guide describes the full range of choices.

The result is a broadband millimeter-wave solution that enhances device characterization and modeling for on-wafer and connectorized measurements. To ensure accurate and repeatable on-wafer results, the N5290/91A solution is also compatible with the wafer-level measurement solution (WMS) created by Keysight and solution-partner Cascade Microtech.

The Keysight N5290A and N5291A broadband millimeter-wave network analyzers enhance device modeling by delivering stable, accurate measurements-on-wafer or connectorized.

Calibrate for better accuracy


Create accurate device models

Calibration helps you ensure better results across the entire frequency range of your design. That's 900 Hz to 120 GHz with our broadband millimeter-wave network analyzers.

In the N5290/91A, the calibration process uses an improved-accuracy database that supports a 1.0 mm calibration kit and a 1.0 mm verification kit. The purpose-built calibration kit and new DC-to-120 GHz power sensor provide traceable measurements that reduce uncertainty through accurate characterization of residual calibration errors. In addition, automatic fixture de-embedding and removal ensures greater accuracy in calibration at the probe tips and enhances the accuracy of on-wafer measurements.

The companion compact frequency-extender modules include ruggedized 1.0 mm test ports to ensure repeatable connections day after day, measurement to measurement. This reduces calibration uncertainty and further improves your system-level measurement precision.






The combination of calibration, fixture de-embedding and fixture removal enhances the accuracy of on-wafer measurements.

Calibrate >

Accelerate complex test plans



Simplify MMIC testing

New-generation monolithic microwave integrated circuits (MMICs) include components that operate at baseband, RF, microwave and millimeter-wave. A vector network analyzer (VNA) with single-sweep coverage from hertz to gigahertz enables you to test all those components in one test setup.

The need to connect, disconnect and reconnect a MMIC to multiple analyzers is inconvenient and time-consuming. The solution is a VNA that has a single-connection, multiple-measurement (SCMM) architecture. In the PNA-X, SCMM lets you measure passive or active devices with one set of connections: S-parameters, noise figure, gain compression, THD, IMD, and spectrum analysis.


Control of source phase and frequency offset simplifies testing of I/Q modulators and converters as well as differential mixers and amplifiers. Precise control of relative phase between sources lets you eliminate hybrid couplers and baluns.

5 C A 🖾 💼 Q 💼 🙃	Markor I 80 GHz	Hardkey	a X
STD GCA DIQ SA Low Freq. SCM		Index	-
40 521 LogM 100049 20008 Tr 2 343 LogM 100049 00048 40 7 8000 900 000 Core 450 db 1 60000 900 000 Core 50 000 db	Tr 11 S21 LogM 1530/69 000/8 * 1 at 100 000 000 CHz + /3 et	Prev	lind
	20	Trace	Charm
	•	Depkiny	SIL
		Mag	Farm
E -ch: Star 900.000 Hz - Stop 125.000 GHz	Ch2 8/03 (min) Ch2 GCA Start 100000 MHz - Stap 125,000 GHz		Fain
T+42 \$33LegM1000.8V 000.81 1 2080 000.00012-6 1559 as	Ti 4 Pres_F1 Light 10.00x89 0.00x80 5 0.000 000 000 0 300 0 30 00 000	Scale	Mat
** 5.8 ********** **************************	>2 100 000 000 ° 1 24 dt	Avg BW	ON
a		Marker	Scare
30	*	-	40
43 Ch5. Start. 900.000 H2 - Store 200000 GH2	-45 Ch3 (H0/Hell Start 1920) - CW 50,000 GHz Stop 100.001	Heg	Howe
Tr 45 S21 LogM 20 00dB/ 60.0dB	Tr 16 8 LogM 10.00d8/ 0.00d8m	Sweep	Tri99
20 1: 2,000,000,000 GH tz +1,52,004 + 2: 55,000,000, MH tz -60,33,004	-10 1: 30.000.000.000 Cills -0.39 d3m 2: 60.000.000 Cills -42.22 d3m	LIS State	_
20 80 The	-30 3 20 000 001 400 Caliz -45.68 dSm -50 > 4: 119.976 003 700 Caliz -70.64 dSm	Recal	Mac
-100 -100 -100 -100 -100 -100 -100 -100	70	System	Und
140	00	linp	Prese
22 Ch5. Start 000 000 Hz Stop 2 00000 GHz	Ch4.SA Start 10.0000 GHz Stop 125.000 GHz		

Greater integration inside MMICs and other wideband designs often means testing more functions per device through fewer access points. SCMM is the most convenient and effective solution.

Accelerate >

Simplify measurement configuration



Speed through complex tasks with measurement applications

To help you save time—and ensure correct configuration of complex tasks—our network analyzer software tools will help you achieve deeper insights into device performance:

- **Scalar mixer/converter:** Supports scalar characterization of mixers and frequency converters
- **Gain-compression:** Provides complete characterization of amplifiers and frequency converters
- Noise-figure: Enables further characterization of frequency converters
- Differential and I/Q devices: Simplifies testing of amplifiers and mixers
- Spectrum analyzer: Provides calibrated multi-channel spectrum analysis

These applications are touch-enabled, providing a more intuitive way to investigate, characterize, and troubleshoot broadband millimeter-wave devices.

Another point: transportable software licensing lets you buy one copy of an application and share it between multiple instruments. This maximizes utilization by letting you and your teammates assign needed functionality to a specific instrument, when and where it's needed.

Select Configuration			ame N5291A Broadband	Test Set	N5292A -
Standard V5291A B	PNA iroødbaad		nable Modules: 😢 Port 1 🛛 😢 Por	t 2 Port S	Port 4
New		Remove	Test Set IF	6	Installation Cal
Frequenc Port	Type	Start	Stop		
Port 1	Module	10.000000000 MH	z 125.000000000 GHz		
	Module	10.000000000 MH	z 125.000000000 GHz		
Port 2		10.000000000 MH	z 125.000000000 GHz		
	Module				
Port 2	Module Module	10.000000000 MH	z 125.000000000 GHz		

The touch-based interface makes analysis more intuitive, and it includes task-specific screens such as Millimeter Configuration that guide new or infrequent users and help ensure better results.


Simplify >

Reduce your total cost of test

Utilize wider coverage and multi-setup calibration

Wider frequency coverage helps reduce the cost of your test solution. For example, a 900 Hz start frequency in a millimeter-wave network analyzer eliminates the need to purchase a dedicated low-frequency VNA. Two more advantages: moving the DUT between fewer test stations increases yield by reducing the likelihood of damage; and using one analyzer reduces complexity by streamlining the development of test system software.


Optimizing the calibration process will further reduce your cost of test. It starts with the ability to maintain a single calibration across multiple setups. This requires exceptional stability in the test system over an extended period of time during the entire test cycle or production run. In the N5290/91A, the "cal all" feature enables you to perform one calibration and apply it to multiple measurement setups.



With magnitude stability of less than 0.015 dB, our broadband millimeter-wave network analyzers can use a single calibration for 24 hours while also maintaining measurement uncertainty.

Reduce >

Optimize device performance at millimeter-wave frequencies



Enhance device modeling with stable, accurate measurements—on-wafer or connectorized using Keysight's broadband millimeter-wave network analyzers. Core elements are a PNA or PNA-X network analyzer along with compact frequency extenders, a test-set controller, and advanced measurement applications.

With these solutions, you can reach for unrivaled excellence in your measurements and designs up to 120 GHz.

Get the details at www.keysight.com/find/N5291A





Build confidence in millimeter-wave design and test

It's easy to underestimate the challenges that arise at these frequencies. That's why Keysight continues to bring you easier access to accurate, repeatable results at everhigher frequencies and wider bandwidths.

Tap into our millimeter-wave expertise and discover innovative tools for design, simulation, test and analysis.

See our growing range of solutions at www.keysight.com/find/millimeter-wave



This information is subject to change without notice. © Keysight Technologies, 2017 Published in USA, August 1, 2017 5992-2490EN www.keysight.com